
# **Advanced Intermetallic Alloys**

The energy utilization and efficiency of industrial processes can be improved by the utilization of high temperature corrosion resistant advanced intermetallic alloys

### Objective:

Provide alloy design, processing, fabrication, and materials property capabilities to develop and enable the use of advanced intermetallic alloys in high performance applications

## Advanced Ni<sub>3</sub>Al alloys



s the max	imum i	in mod use too			
Composition, wiffs					
N	H	01	Mo	20	8
Bulance	8.0	7.7	1.43	1.5	0.008
Sulance	8.1	5.2	7.0	0.13	0.005
	s the max	mical compositions the maximum of the 1200°C  No. Al. Subsect. 8.0 Subsect. 8.1	s the maximum use ten N° to 1200°C  Composite N A C  Bulance 8.0 7.7	is the maximum use temperature to 1200°C  Composition, with Ni Ai Gr Mo Balance 8.0 7.7 1.43	s the maximum use temperature of the 1209°C  Compositor, wife  N N Gr Mo 2r  Balance 8.0 7.7 1.43 1.5

Improved high temperature mechanical properties of Ni3Al enables higher thermal efficiencies in industrial processes

## FeAl alloys




Centrifugally cast FeAl tube


40	H <sub>2</sub> - 11/CH <sub>0</sub> , 1000°C	(INCO data on ORNL
30		alloys)
20		na cont had, provident
10	/	
0	<b>/</b>	
	(carburtration Res	(stance)
-40		

Superior carburization resistance of FeAI alloys will enable more efficient chemical processing

#### **Partners**

















# Ni<sub>3</sub>Si alloys



Multi-pass welds made in cast bars confirm that some Ni3Si alloys have excellent weldability

Ni <sub>3</sub> Si alleys with Nb and Ti have exceptional corrector resistance in boiling sulphuric acid	
- Annaharata aktion	

	Cornodion rate, milts/year			
Composition, at%	60% H <sub>2</sub> 50 <sub>1</sub>	77% H <sub>2</sub> 50 <sub>1</sub>		
NI-18.852	3640	35		
NE 18,95E 1,2NB	358	1		
No. 18, 950-31,271	160			

Development of castable and weldable Ni<sub>3</sub>Si alloys will enable fabrication of complex components for use in chemical process systems



# Research and Development Sponsored by

Industrial Materials for the Future (IMF) Program
Office of Industrial Technologies, Energy Efficiency and Renewable Energy;
and also based on research and development funded by Energy Research,
U.S. Department of Energy



# **Advanced Intermetallic Alloys**

The energy utilization and efficiency of manufacturing processes can be improved by operating at the higher temperatures or with the better environmental resistance provided by advanced intermetallic alloys.

**Goal**: Provide the processing, fabrication and material property expertise necessary to implement advanced intermetallic alloys in high performance applications that can benefit the most from the unique properties of these alloys.

There is a need in the manufacturing and power generation/cogeneration industries to push the safe service temperatures of metallic alloys ever higher. Increasing the operating temperature of some processes can improve their thermodynamic efficiency. In other cases, increases in operating temperature can reduce the residence time of materials at critical reaction temperatures. Each of these conditions can result in significant energy savings by promoting more efficient energy utilization, increased productivity, and reduced process down time. Likewise, there is a need to identify and utilize intermetallic alloys with improved or unique environmental resistance, which can result in similar efficiency benefits and energy savings. Currently, a Ni<sub>3</sub>Al alloy is being developed which can withstand service temperatures of 100-150 °C higher than commercial Ni<sub>3</sub>Al alloys. Other alloys under study are based on the intermetallic alloys FeAl. Under certain conditions, these alloys have resistance to carburization and sulfidation that far exceeds that of most commercial alloys. Also being developed are alloys based on Ni<sub>3</sub>Si. Initial testing indicates that the Ni<sub>3</sub>Si alloys have good mechanical properties coupled with excellent resistance to oxidizing conditions, such as in sulfuric acid and sea water, and to ammonia at temperatures up to 900°C.

#### Contacts:

Vinod Sikka
Oak Ridge National Laboratory
1 Bethel Valley Rd.
Oak Ridge, TN 37831-6083

Phone: (865) 574-5112 E-mail: sikkavk@ornl.gov

Michael Santella Oak Ridge National Laboratory 1 Bethel Valley Rd. Oak Ridge, TN 37831-6096

Phone: (865) 574-4805 E-mail: santellaml@ornl.gov Philip Maziasz
Oak Ridge National Laboratory
1 Bethel Valley Rd.
Oak Ridge, TN 37831-6115

Phone: (856) 574-5082 E-mail: maziaszpj@ornl.gov